

# SLT Series Total Station

## Data Specifications

MODEL	SLT2	SLT5
<b>ANGLE MEASUREMENT</b>		
Minimum Readout	1" (0.3 mgon), 5" (1.5 mgon), 10" (3 mgon)	
Method	Absolute encoding	
Accuracy	2"	5"
Compensator System	Dual-axis	
Compensator Range	±3'	
Compensator Setting Accuracy	1"	
<b>DISTANCE MEASUREMENT WITH REFLECTOR</b>		
Single Prism	3,000m	
Three Prisms	5,000m	
Reflective Sheet	800m	
Accuracy	2mm + 1.5ppm	
Measuring Time	Fine	1s
	Quick	0.8s
	Tracking	0.5s
<b>DISTANCE MEASUREMENT WITHOUT REFLECTOR</b>		
Range	800m	
Single Prism	> 7,500m	
Accuracy	3mm + 2ppm	
Measuring Time	1.5s	
<b>TELESCOPE</b>		
Magnification	30x	
Image	Erect	
Field of View	1°20' (2.4m at 100m)	
Min. Focusing Range	1.5m	
Reticle	Illuminated	
Effective Diameter of Objective	40mm/50mm (EDM)	
Resolving Power	3"	
<b>LASER PLUMMET</b>		
Type	Laser point, 4 brightness levels adjustment/ Optical plummet (optional)	
Centering Accuracy	1mm at 1.5m instrument height	
<b>OPERATION</b>		
System	Real-time operating system	
Display	Dual face high resolution 256 colour display	
Keyboard	2 sides alpha-numerical back-lit keyboard	
Temperature and Pressure Sensor	Built-in	
<b>GENERAL</b>		
Environmental	IP65 environmental protection	
	Humidity 95% (non-condensing)	
	Temperature	-20°C to 50°C Operating -40°C to 70°C Storage
Physical Properties	Resolution	320 x 240 pixels
	Weight	≤5.5kg (12lb) including battery
	Battery	7.4VDC / 3000 mAH
	Operation	Optimally 18 hours
	Internal Storage	Approx. 20,000 Points

# SLT Series

## Total Station



**Headquarters:**  
 Datavägen 21B  
 SE-436 32 Askim, Sweden  
 info@satlabgps.com

**Regional Offices:**  
 Warsaw, Poland  
 Jičín, Czech Republic  
 Ankara, Turkey  
 Scottsdale, USA  
 Singapore  
 Hong Kong  
 Dubai, UAE

[www.satlab.com.se](http://www.satlab.com.se)



The SLT Series has a fast and powerful reflectorless EDM (0.8 seconds) that is designed to provide advanced accuracy with an efficient workflow in a sleek body. In order to ensure long-term operation in adverse weather conditions, various environmental tests such as vibration, drop, temperature, and humidity were performed to achieve the highest quality.



Swedish Quality



30x Magnification



Single Button Operation



Reflectorless



Durable

### Maximum flexibility and great performance

Designed to overcome challenging work situations, Satlab has combined the best field technologies and specialized engineering features to ensure that the SLT Series provides the highest level of accuracy. Capture measurements faster and easier with our intuitive onboard software (Satcont) using a dual colour LCD display.



### Applications

- Road Works
- Land Surveying
- Topography and As-built
- Construction Survey and Layout
- Foundation and Exterior

### Increased efficiency with enhanced accuracy

The SLT Series is the most ideal entry-level work site surveying tool that offers flexibility and reliability, enabling you to get the job done without sacrificing on functionality. Equipped with a fast and reflectorless EDM, as well as the Satcont onboard software, the SLT Series is built to last.

### Delivering quality equipment

Manufactured in an ISO, and CE certified factory, each total station is made with proper protocol and procedure that adheres to every operating aspect as well as stringent quality assurance checks that ensures the highest quality.

#### TECHNICAL SUPPORT

Satlab offers online resources and a professional support network available worldwide.

