

SL11 Rugged Tablet

Data Specifications

Configuration

OS & Processor

Android 15.0, 2.0 GHz, advanced octa-core high-speed processor

Storage

8 GB RAM +128 GB ROM, support 2TB SD card

Display Resolution Camera

10.1-inch display, touchable screen
1920 x 1200, 500 nit, readable under the sun
32M pixels rear camera, 8M pixels front camera, autofocus, highlight LED flash
L-sensor (Compatible Design), G-sensor, Gyroscope, E-compass

Built-in Sensor

GNSS

Signal Tracking

GPS/ Galileo / GLONASS / BeiDou / QZSS Support SBAS

Communications

USB

USB 2.0, Type-C, OTG function

SIM

Support, Nano SIM

Network 4G modem

GSM: 850/900/1800/1900
WCDMA: B1/B2/B4/B5/B8
LTE-TDD: B34/B38/B39/B40/B41
LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12 /B13/ B17/B18/B19/B20/B25/B26/B28

Wi-Fi

Wi-Fi, IEEE 802.11a/b/g/n/ac

Bluetooth NFC

(Dual Band 2.4&5 GHz)
Bluetooth 5.3, BLE
Support NFC function

Battery^[1]

Capacity

3.8 V 9200 mAh, Removable Battery

Bettery life

≥ 8 h

Charging time

4 .5h, support Fast charging: QC 3.0, 18 W

Physical

Size

278 mm × 190 mm × 13.3 mm

Weight

800 g (with battery)

Shock

1.2 m fall onto concrete

Dustproof & Waterproof

IP67 (according to IEC 60529)

Humidity

0 - 95% RH (without condensation)

Temperature

Working: -20 °C ~ +60 °C
Storage: -40 °C ~ +70 °C



SL11 GNSS RTK Rugged Tablet



Headquarters:
Stora Ävägen 21, 436 34 ASKIM,
Sweden

Regional Offices:
Budapest, Hungary
Ankara, Turkey
Dubai, UAE
New Delhi, India
Scottsdale, USA
Tokyo, Japan
Hong Kong, China

www.satlab.com.se

*Description and Specifications are subject to change without notice.
[1] The battery operating time is related to the operating environment, operating temperature and battery life.