

SL15

Rugged Pad



CE



SL15 Rugged Pad

Data Specifications

SYSTEM

Operating System	Android 9.0
CPU	MSM8953 Octa-core (2.2GHZ)
GPU	Adreno 506 650MHz, 1920x1200 @ 60fps UBWC OpenCL2.0 FP, DX12, OpenGL ES 3.1+, AEP
Supported Capacity RAM	4GB LPDDR3
ROM	64GB EMMC
G Sensor	Gravity acceleration sensor
Sensors	Magnetism Sensor (Compass)
Audio Features	1x internal microphones, 1x built-in speakers
Integrated WLAN	WLAN 802.11 a/b/g/n/ac
Bluetooth	BT4.2(BLE) class1.5 transmission distance: 10m
Network	3G/4G

MULTI-MEDIA

Camera	Front Camera: 5.0MP Rear Camera: 13MP auto-focus with flashlight
--------	---

DISPLAY

Screen	10.1" inch (16:10) Gorilla Glass TP
Brightness	Minimum 700cd/m ²
Resolution	800 x 1280

INTERFACE CONFIGURATION

Ports	USB 2.0 Android OTG TypeC Put 2 x Micro Sim card Slot Put TF slot support Max 128G 12pin Pogo Pin DC Connector 3.5mm Standard Earphone Jack
-------	--

ACCESSORIES

Standard	OTG Cable USB Cable Power Adaptor: AC100V - 240V 50Hz/60Hz output (DC 5v/3A)
Optional	Docking Charger, Car Holder, Straps

GENERAL

Environmental	IP65/MIL-STD-810G Humidity 95% (non-condensing) Drop resistant to 1.2m Temperature -10°C to 60°C Operation -30°C to 70°C Storage
---------------	--

Physical Properties

Size: 280mm x 180mm x 20.5mm
Weight: 1068g
Battery Capacity: Li-on 3.7V/10000mAH (4G)
Battery Lifetime: >8h



Headquarters:
Datavägen 21B
SE-436 32 Askim, Sweden
info@satlab.com.se

Regional Offices:
Warsaw, Poland
Jičín, Czech Republic
Ankara, Turkey
Scottsdale, USA
Singapore
Hong Kong, China
Dubai, UAE

www.satlab.com.se

